

Options and Accessories / Series 200 Commercial Sheet Door

Part 1 - GENERAL

1.01 DESCRIPTION

A. Type: Options and Accessories for Continuous Sheet Doors to be manufactured by Asta Door Corporation.

1.02 RELATED WORK

A. Opening preparation, access panels, finish or field painting are in the scope of the work of other sections or trades.

Part 2 - PRODUCT

2.01 CURTAIN

A. Outside Mount: curtain to be assembled inside out for outside mounting.

B. Top Draft Stop: E.P.D.M. weatherseal riveted to curtain is to seal against header.

C. Side Draft Stop: ethafoam material to be attached to curtain edges.

D. Vision Panel: to be 22" (558.8mm) X 7 1/2" (190.5mm) vision hole through curtain covered by clear lexan panel.

E. Vent: to be 14" (355.6mm) X 6" (152.4mm) vent hole through bottom of curtain covered by louvers and wire mesh.

F. Sloped Bottom Bar: bottom bar shall conform to slope in finished floor (as indicated on architectural drawings).

2.02 OPERATION

A. Manual Lift: to be operated by nylon rope attached to bottom angle.

B. Chain Thru Wall: to be chain hoist operated through the wall.

C. Motor: to be motor operated (see electric operators).

2.03 GUIDE ASSEMBLY

A. Heavy Duty: to be roll formed 12 gauge galvanized steel (standard on larger sizes, consult factory)

2.04 LOCKING

A. Cylinder Lock available. (consult factory)
(NOTE: use electric interlocks with motorized doors.)

2.05 HOODS

A. Hood: to be 26 gauge galvanized steel with baked epoxy primer and baked polyester top coat and enclose coil.