



GUIDE TYPE	A	B	C	D	E	TYPE	DEDUCT
2	5.7/8"	3.3/16"	4"	2.9/16"	1.1/4"	2	12"
3	6.3/8"	3.9/16"	4.3/8"	2.15/16"	1.1/4"	3	12"
4	6.3/4"	3.15/16"	4.3/4"	2.3/4"	1.1/4"	4	12.3/4"
2(W/L)	6.3/8"	3.3/16"	4"	2.9/16"	1.1/2"	2(W/L)	12.3/4"
3(W/L)	6.3/8"	3.9/16"	4.3/8"	2.15/16"	1.1/2"	3(W/L)	12.3/4"
4(W/L)	6.3/4"	3.15/16"	4.3/4"	2.3/4"	1.1/2"	4(W/L)	13.1/2"
5(W/L)	6.3/4"	4"	4.3/4"	2.3/4"	1.1/2"	5(W/L)	13.1/2"
6(W/L)	8.3/4"	6.1/4"	7.1/4"	3.1/2"	1.1/2"	6(W/L)	17.1/2"

**GENERAL NOTES**

SLATS/HOOD: SELECT FINISH OPTION BELOW (HOOD INCLUDES WEATHER BARRIER)

GRAY POLYESTER TOP COAT

WHITE POLYESTER TOP COAT

OTHER SURFACES:

SHOP COAT BLACK PRIMER

OPERATION:

RIGHT HAND SHOWN, LEFT HAND OPPOSITE

GUIDES:

STRUCTURAL STEEL ANGLES OF 3/16" MINIMUM THICKNESS

WITH PVC WEATHER SEAL

BOTTOM BAR:

TWO 2"x2"x1/8" STEEL ANGLES WITH PVC BULB ASTRAGAL

MARK	QTY.	OPENING SIZE	OPERATION	RH	CLEARANCES	OPTION	PROJECT:
		WIDTH "W"		LH	"X+2"	"V"	ARCHITECT:
		HEIGHT "H"					CONTRACTOR:
							DISTRIBUTOR:
							DATE:
							OF:
							BY:
							REF#:
							DATE:

ASTA Door Corporation is not responsible for the use of improper installation procedures, structural supports as well as field inspection prior to manufacturing and installation.

APPROVAL SIGNATURE: \_\_\_\_\_

**600 SERIES-INSULATED-BETWEEN JAMB-VISION LITES (H MOTOR)**

4255 McEver Industrial Dr.  
Acworth, GA 30101  
PH(770) 924-2800  
Fax(770) 974-1455  
www.astadoor.com